HEALTH AND SAFETY PLAN FOR SCREENING SITE INSPECTION FIELD WORK DOYLE, FRANK J. (a.k.a Frank J. Doyle Transformer Site)

Prepared by

Texas Natural Resource Conservation Commission Superfund Site Discovery and Assessment Team Austin, Texas

Reviewed and approved by

Site Safety Officer:		
. 	Name	Date
Site Investigation: Manager	Name 1	12/17/97 Date
PA/SI Program Manage Representative:	Name Sulv	12/18/97 Date
TNRCC Central Office Health & Safety Representative:	Name (13/18/97 Date

December 1997

9820279

Contents

<u>Pa</u>	ge
Emergency Contacts	. iv
Section 1: Introduction	1
Section 2: Site Information	2 3
Section 3: Project Team Organization	.6
Section 4: Safety and Health Risk Analysis	10 .10 .10
Section 5: Personnel Protection Equipment and Monitoring	.18 .18 .19
Section 6: Frequency and Types of Air Monitoring	21 23
Section 7: Accident Prevention and Contingency Plan	.24 24
Personal Injury Evacuation Procedures	25

SECTION 2

SITE INFORMATION

GENERAL INFORMATION

Site: Doyle, Frank J., aka: Frank J. Doyle Transformer Site, TXD980865109

Location: The Frank J. Doyle Transformer site is an active metal salvage yard (SWR# 80951) that occupies 0.6 acres located at 305 E. Cottonwood Street, Leonard, Texas in Fannin County. The site consists of a shop and storage areas surrounded by a 6'-high wooden perimeter fence. The geographic center of the site is 33° 23' 23" N Latitude and 96° 14' 34" W. The site is located in a residential area in the northeast portion of the city adjacent to Leonard High School. The alleyway south of the site is accessed by the public frequently and the nearest residence is located 40' south of the site.

Mailing Address: F. J. Doyle Salvage Transformers 305 E. Cottonwood Street, Box 312 Leonard, TX 75452

Proposed date of field work: January, 1998

Hazard Assessment: ___ High __ Medium __ Low
__ None __ Unknown

Site description: The owner, Frank J. Doyle, began salvage operations in 1974 and operated at the site until his retirement in January 1997. The owner resides next to the site. His son, Gary Doyle, now operates the facility. Used transformers are received from suppliers in Texas, Oklahoma, Louisiana and Arkansas, off-loaded, drained, copper cores removed, baked to remove varnish, paper and residual oil and stripped for recoverable metals. Drained transformer oils are stored on-site in tanks or drums and subsequently shipped to a recycler. Suppliers are required to test shipped transformers for PCBs <40 parts per million (ppm). According to the owner, transformers were not tested prior to 1980.

Based on an EPA site assessment and results of soil samples collected on July 10-12, 1995, the site has three on-site areas (depth 0"-24") with polychlorinated biphenyls (PCB) contaminated soils ranging from 2.7 mg/kg to 1,590 mg/kg and three off-site areas ranging from 1.57 mg/kg to 2,730 mg/kg at varying depths (0"-6", 6"-12", 12"-18" and 18"-24") along the site perimeter. A May 20, 1997 PA identified two city wells and adjacent residential yards/public schools as potential targets.

SCOPE OF WORK SUMMARY

The field team will collect groundwater and soil samples. Samples to be collected include a total of four (4) groundwater samples, nineteen (19) soil samples, two (2) rinsate samples and three (3) field blanks. These include three (3) background soil samples collected from unaffected upwind/upgradient locations within one mile of the site and one (1) background groundwater sample collected from an off-site upgradient public drinking water well located within two miles of the site for attribution of site contaminants. A duplicate sample will be collected for each matrix each day.

All samples will be collected according to the procedures outlined in the QAPP (Appendix E).

No air samples are planned to assess releases to the air pathway. In addition, no sediment samples are anticipated since there are no perennial streams or receptor bodies of water located within the required 2-mile target distance limit.

SITE/CHEMICAL CHARACTERISTICS

Chemical type(s):	Liquid	Solid	Sludge	Gas
Characteristic(s):	Corrosive	Ignitable	Radioactive	
	Volatile	Toxic	Reactive	•
	Unknown	Other		

Summary of known wastes: See below.

List of hazardous substances detected onsite: polychlorinated biphenyls (Aroclor 1260) detected in soils adjacent to on-site waste management units and off site.

Description of all known waste disposal areas on site: Know waste disposal areas include: (1) surface soils in the transformer storage area located in the southeast portion of the site, (2) soils adjacent to the container storage area located in the southwest portion of the site, and (3) soils in the transformer off-load area located in the north central portion of the site.

Site waste management history: The site has been investigated for suspected PCB-contaminated soils by the EPA since 1990. PCB contamination suspected from discharged or spilled transformer oils were initially investigated by the EPA on July

HEALTH AND SAFETY PLAN FOR SCREENING SITE INSPECTION FIELD WORK DOYLE, FRANK J. (a.k.a Frank J. Doyle Transformer Site)

Prepared by

Texas Natural Resource Conservation Commission
Superfund Site Discovery and Assessment Team
Austin, Texas

Reviewed and approved by

Site Safety Officer:		•
	Name	Date
Site Investigation:	Spro D. pm	12/17/97
Manager	Name	Date / /
PA/SI Program Manage	er Alle 1. Shilv	12/18/97
Representative:	Name	Date
TNRCC Central Office	I self outer	12/18/97
Health & Safety	Name	Date

December 1997

Contents

	Page
Emergency Contacts	iv
Section 1: Introduction	1
Section 2: Site Information	2 3
Section 3: Project Team Organization	6
Section 4: Safety and Health Risk Analysis	10 10 10
Section 5: Personnel Protection Equipment and Monitoring	18 18 19
Section 6: Frequency and Types of Air Monitoring	21 23
Section 7: Accident Prevention and Contingency Plan	24 24
Personal Injury Evacuation Procedures	25

SECTION 2

SITE INFORMATION

GENERAL INFORMATION

Site: Doyle, Frank J., aka: Frank J. Doyle Transformer Site, TXD980865109

Location: The Frank J. Doyle Transformer site is an active metal salvage yard (SWR# 80951) that occupies 0.6 acres located at 305 E. Cottonwood Street, Leonard, Texas in Fannin County. The site consists of a shop and storage areas surrounded by a 6'-high wooden perimeter fence. The geographic center of the site is 33° 23' 23" N Latitude and 96° 14' 34" W. The site is located in a residential area in the northeast portion of the city adjacent to Leonard High School. The alleyway south of the site is accessed by the public frequently and the nearest residence is located 40' south of the site.

Mailing Address: F. J. Doyle Salvage Transformers 305 E. Cottonwood Street, Box 312 Leonard, TX 75452

Proposed date of field work: January, 1998

Hazard Assessment: ___ High __ Medium __ Low
__ None __ Unknown

Site description: The owner, Frank J. Doyle, began salvage operations in 1974 and operated at the site until his retirement in January 1997. The owner resides next to the site. His son, Gary Doyle, now operates the facility. Used transformers are received from suppliers in Texas, Oklahoma, Louisiana and Arkansas, off-loaded, drained, copper cores removed, baked to remove varnish, paper and residual oil and stripped for recoverable metals. Drained transformer oils are stored on-site in tanks or drums and subsequently shipped to a recycler. Suppliers are required to test shipped transformers for PCBs <40 parts per million (ppm). According to the owner, transformers were not tested prior to 1980.

Based on an EPA site assessment and results of soil samples collected on July 10-12, 1995, the site has three on-site areas (depth 0"-24") with polychlorinated biphenyls (PCB) contaminated soils ranging from 2.7 mg/kg to 1,590 mg/kg and three off-site areas ranging from 1.57 mg/kg to 2,730 mg/kg at varying depths (0"-6", 6"-12", 12"-18" and 18"-24") along the site perimeter. A May 20, 1997 PA identified two city wells and adjacent residential yards/public schools as potential targets.

SCOPE OF WORK SUMMARY

The field team will collect groundwater and soil samples. Samples to be collected include a total of four (4) groundwater samples, nineteen (19) soil samples, two (2) rinsate samples and three (3) field blanks. These include three (3) background soil samples collected from unaffected upwind/upgradient locations within one mile of the site and one (1) background groundwater sample collected from an off-site upgradient public drinking water well located within two miles of the site for attribution of site contaminants. A duplicate sample will be collected for each matrix each day.

All samples will be collected according to the procedures outlined in the QAPP (Appendix E).

No air samples are planned to assess releases to the air pathway. In addition, no sediment samples are anticipated since there are no perennial streams or receptor bodies of water located within the required 2-mile target distance limit.

SITE/CHEMICAL CHARACTERISTICS

Chemical type(s):	Liquid	_ ✓ Solid	Sludge Gas
Characteristic(s):	Corrosive	Ignitable	Radioactive
	Volatile	Toxic	Reactive
	Unknown	Other	·

Summary of known wastes: See below.

List of hazardous substances detected onsite: polychlorinated biphenyls (Aroclor 1260) detected in soils adjacent to on-site waste management units and off site.

Description of all known waste disposal areas on site: Know waste disposal areas include: (1) surface soils in the transformer storage area located in the southeast portion of the site, (2) soils adjacent to the container storage area located in the southwest portion of the site, and (3) soils in the transformer off-load area located in the north central portion of the site.

Site waste management history: The site has been investigated for suspected PCB-contaminated soils by the EPA since 1990. PCB contamination suspected from discharged or spilled transformer oils were initially investigated by the EPA on July